

# Features Es







### Reassuring Foundation

Adopted the most stable and safe lithium iron phosphate (LiFePO4) battery

#### High Safety

Build-in BMS, protection functions of discharge, over charge,

over current, high temperature and low temperature

#### All in Control

Equipped with RS232/RS485/CAN bus ports, the most important with bluetooth and WIFI function

#### High Cost Performance

More than 6000 cycles, 10 years service life, providing long-term energy for your home

#### **Arbitrary Extension**

The same capacity of the battery can be freely expanded to meet the electricity demand in an all-round way

#### Perfect Match

Compatible with inverters of most main stream brands on the market



## Technical Specification

Model	BR-WM-LV 5KWH	BR-WM-LV 10KWH	
Main Parameter			
Cell Technology	Lithium-iron Phosphate (LiFePO4)		
Nominal Energy	5kWh	10kWh	
Round-Trip Efficiency	98%		
Scalability	Max. 15 Modules in Parallel		
Dimensions(L/W/H)	615*500*160mm	615*580*215mm	
Weight	53kg	88kg	
Installation	Indoor		
\\/orront\/	10 Years Prod	10 Years Product Warranty	
Warranty	15 Years Performance Warranty		
Electrical Parameter			
Nominal Voltage	51.2V		
Nominal Capacity	100Ah	200Ah	
Max Charge Current	100A	100A	
Max. Cont. Charge Current	100A	100A	
Max Discharge Current	100A	100A	
Max. Cont. Discharge Current	100A	100A	
Operating Voltage Range	43.2V – 57.6V		
Charge Cut-Off Voltage	58.4V		
Discharge Cut-Off Voltage	43.2V		
General Parameter			
Cycle Life	≥6000 Times (80%DoD)		
Service Life	10 Years		
Protection Rating	IP55		
Display	SOC Status Indicator, LED Indicator		
Communication	RS485, RS232, CAN		
Charge Temperature Range	0°C~60°C (Under 0°C extra heating mechanism)		
Discharge Temperature Range	–20°C~60°C (Under 0°C work with reduced capacity)		
Storage Temperature Range	–40°C~55°C @ 60%±25% relative humidity		
Compatible Inverters	SMA, Victron Energy, Deye, Goodwe, Growatt, Sermatec, etc.		

<sup>\*</sup> Compatible tests with different brands of inverter are continuously, updates will be periodically.

<sup>\*\*</sup> Under specific test conditions.